

SEAL-KRETE INC

-- WATERPROOFING SEALER

=====
MSDS Safety Information
=====

FSC: 8030
MSDS Date: 02/25/1997
MSDS Num: CGSZF
LIIN: 00N031655
Product ID: WATERPROOFING SEALER
MFN: 02
Responsible Party
Cage: SEALK
Name: SEAL-KRETE INC
Address: 306 GANDY RD
City: AUBURNDALE FL 33823
Info Phone Number: 800-323-7357
Emergency Phone Number: 800-424-9300 (CHEMTREC)
Published: Y

=====
Contractor Summary
=====

Cage: SEALK
Name: SEAL-KRETE INC
Address: 306 GANDY RD
City: AUBURNDALE FL 33823-1527
Phone: 800-323-7357

=====
Ingredients
=====

RTECS #: 1000314NH
Name: NON-HAZARDOUS INGREDIENTS
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

RTECS #: 99999999VO
Name: VOLATILE ORGANIC COMPOUND: <6 G/L
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: ACUTE: POSSIBLE IRRITATION AND DISCOMFORT. INHALATION:
NONE EXPECTED, HOWEVER CERTAIN INDIVIDUALS MAY BE SENSITIZED AND EXPERIENCE
MINOR NAUSEA OR HEADACHE. SKIN: NONE EXPECTED, HOWEVER, PROLONGED CONTACT
MAY CAUSE IRRITATION. EYES: CONTACT WITH EYES MAY CAUSE IRRITATION.
INGESTION: MAY CAUSE GASTRIC (EFTS OF OVEREXP)
Explanation Of Carcinogenicity: NOT RELEVANT
Signs And Symptoms Of Overexposure: HLTH HAZ: DISTRESS, VOMITING AND
DIARRHEA. CHRONIC: NO KNOWN EFFECTS HAVE BEEN ESTABLISHED.
Medical Cond Aggravated By Exposure: PREEXISTING SKIN, EYE OR RESPIRATORY

DISORDERS MAY BECOME AGGRAVATED THROUGH PROLONGED EXPOSURE.

First Aid: INHAL: REMOVE TO FRESH AIR. IF SYMPS PERSIT SEEK MED ATT. SKIN: REMOVE CONTAMD CLTHG; WASH AFFECTED AREA W/SOAP & WATER. LAUNDER CONTAM CLTHG BEFORE REUSE. IF IRRIT PERSISTS, SEEK MED ATTN. EYES: FLUSH EYES W/CLEAR RUNNING WATER FOR AT LEAS T 15 MIN WHILE HOLDING EYELIDS OPEN. IF IRRIT PERSISTS, SEEK MED ATTN. INGEST: GIVE TWO GLASSES OF WATER FOR DILUTION; INDUCE VOMITING BY HAVING VICTIM (SUPDAT)

=====
Handling and Disposal
=====

Spill Release Procedures: SMALL SPILLS - WASH TO SANITARY SEWER WITH PLENTY OF WATER. LARGE SPILLS - CONFINE SPILL, SOAK UP WITH APPROVED ABSORBENT, SHOVEL PRODUCT INTO APPROVED CONTAINER FOR DISPOSAL. WASH AREA WITH PLENTY OF WATER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSE OF I/A/W LOC, STATE & FED REGS. PRODS CLASSIFIED AS NON-HAZ MAY BECOME HAZ WASTE UPON CNTCT W/OTHER PRODS. REFER TO "40 CFR PROT OF ENVIRONMENT PARTS 260-299" FOR COMPLETE WASTE DISP REGS. CONSULT LOC/STATE/FED EPA BEFORE DISP OF ANY CHEMS.

Handling And Storage Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE; PROTECT CONTAINERS FROM ABUSE; PROTECT FROM EXTREME TEMPERATURES.

Other Precautions: KEEP THIS AND OTHER CHEMICALS OUT OF REACH OF CHILDREN;MINIMIZE BODY CONTACT WITH THIS PRODUCT AS WELL AS ALL CHEMICALS INGENERAL.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: >200F,>93C

Extinguishing Media: CARBON DIOXIDE, WATER FOG, DRY CHEMICAL, CHEMICAL FOAM.

Fire Fighting Procedures: USE NIOSH APPRVD SCBA & FULL PROTECTIVE EQUIPMENT (FP N). DO NOT USE SOLID STREAM OF WATER SINCE STREAM WILL SCATTER & SPREAD FIRE. FINE WATER SPRAY (SUPDAT)

Unusual Fire/Explosion Hazard: CLOSED CNTNRS CAN EXPLODE DUE TO BUILDUP OF PRESS WHEN EXPOSED TO EXTREME HEAT; DO NOT USE DIRECT STREAM OF WATER ON POOL FIRES AS PROD MAY REIGNITE ON (SUPDAT)

=====
Control Measures
=====

Respiratory Protection: NONE REQUIRED. USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN (FP N).

Ventilation: MECHANICAL (GENERAL): RECOMMENDED.

Protective Gloves: IMPERVIOUS GLOVES (FP N).

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER (FP N).

Work Hygienic Practices: PRACTICE SAFE WORKPLACE HABITS. MINIMIZE BODY CONTACT WITH THIS AS WELL AS ALL CHEMICALS IN GENERAL.

Supplemental Safety and Health: PH: 7.9-8.9. FIRE FIGHT PROC: CAN BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL. EXPLO HAZ: WATER SURFACE. CAUTION- MATERIAL WILL SUPPORT COMBUSTION. FIRST AID PROC: PLACE HIS FINGER DOWN HIS THROAT;SEEK MED ATTN. NEVER GIVE ANYTHING BY MOUTH TO UNCON PERSON.

=====
Physical/Chemical Properties
=====

B.P. Text: 212F,100C

Vapor Pres: 17 2 20C

Vapor Density: >1

Spec Gravity: 1.023 (H*20=1)

PH: SUPDAT
Solubility in Water: EMULSIFIABLE
Appearance and Odor: CLEAR TO MILKY WHITE LIQUID; CHARACTERISTIC MILD ODOR.
Percent Volatiles by Volume: 90 WT

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: EXTREME TEMPERATURES.
Materials To Avoid: STRONG OXIDIZERS, STRONG ACIDS.
Hazardous Decomposition Products: THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE, CARBON DIOXIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
HAZCOM Label
=====

Product ID: WATERPROOFING SEALER
Cage: SEALK
Assigned IND: Y
Company Name: SEAL-KRETE INC
Street: 306 GANDY RD
City: AUBURNDALE FL
Zipcode: 33823-1527
Health Emergency Phone: 800-424-9300 (CHEMTREC)
Label Required IND: Y
Date Of Label Review: 03/31/1998
Status Code: C
Label Date: 03/31/1998
Origination Code: G
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: Slight
Reactivity Hazard: None
Hazard And Precautions: ACUTE: POSSIBLE IRRITATION AND DISCOMFORT.
INHALATION: CERTAIN INDIVIDUALS MAY BE SENSITIZED AND EXPERIENCE MINOR NAUSEA OR HEADACHE. SKIN: PROLONGED CONTACT MAY CAUSE IRRITATION. EYES: CONTACT WITH EYES MAY CAUSE IRRITATION. INGESTION: MAY CAUSE GASTRIC

DISTRESS, VOMITING AND DIARRHEA. CHRONIC: NONE LISTED BY MANUFACTURER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.