

EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE VOLUME: 65.3 to 65.3

=====
SECTION IV - FIRE AND EXPLOSION HAZARD DATA
=====

D.O.T. FLAMMABILITY CLASSIFICATION: FLAMMABLE FLASH PT.: 75 F PMCC
LEL: 1.0%

EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers may burst if exposed to extreme heat or fire. Aluminum fire may react with water to form hydrogen gas. Hydrogen gas is flammable and explosive. Toxic gases may form when product burns.

SPECIAL FIREFIGHTING PROCEDURES:

DO NOT use water stream on burning liquid. DO NOT use Halogenated extinguishing agents like Halon or Carbon Tetrachloride
Cool exposed containers with water fog. Use self-contained breathing apparatus.

=====
SECTION V - HEALTH HAZARD DATA
=====

EFFECTS OF OVEREXPOSURE - ACUTE:

Inhalation - Harmful if inhaled. May affect the brain or nervous system, causing dizziness, headache or nausea.

Contact - Causes eye irritation. Contact - Causes skin irritation. Skin Absorption - Hazardous ingredients in this product have the potential to be absorbed through the skin in sufficient quantities to cause systemic toxicity. See Safe Handling and Use Information (Section VIII).

Ingestion - Irritation of the digestive tract and nervous system depression (drowsiness, dizziness, loss of coordination and fatigue). Aspiration Hazard - This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

EFFECTS OF OVEREXPOSURE - CHRONIC:

Skin Contact - Prolonged or repeated exposure may cause dermatitis.

Contains: Ethyl Benzene which has been shown to cause cancer in male rats.

NOTICE: Reports have associated permanent brain and nervous system damage with repeated, prolonged overexposure to solvents among persons engaged in the painting trade. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use Information (Section VIII).

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation - Remove from hazard area, maintain breathing, call physician.

Skin Contact - Remove with soap and water.

Eye Contact - Flush immediately with large amounts of water. Call physician.

Ingestion - Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Call physician.

=====

SECTION VI - REACTIVITY DATA

STABILITY: STABLE under normal conditions HAZARDOUS POLYMERIZATION
WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce carbon dioxide and
carbon monoxide and aluminum oxide.

CONDITIONS TO AVOID: Elevated temperatures and build up of vapors.

INCOMPATIBILITY (MATERIALS TO AVOID): Water, some acids, some caustics,
halogenated hydrocarbons and oxidizers.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Avoid breathing vapors. Use non-sparking
tool to return materials to container. Absorb residue with Fuller's earth.

WASTE DISPOSAL METHOD:

Conventional procedures in compliance with local, state and federal
regulations.

Do not incinerate sealed containers.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Wear a properly fitted vapor/particulate approved by NIOSH/MSHA for use with
paints (TC-23C) during application or sanding and until all vapors and spray
mist are exhausted. In confined spaces or in situations where continuous
sprayoperations are typical, or if proper respirator fit is not possible,
wear a positive-pressure, supplied air respirator (NIOSH/MSHA TC-19C)

VENTILATION:

Adequate to maintain working atmosphere below T.L.V. and L.E.L. (See Sect. II
for ingredient data and concentrations). Mechanical exhaust may be required
in confined areas. Discharge exhaust only in area away from ignition sources.

PROTECTIVE GLOVES: Solvent impermeable gloves are required

EYE PROTECTION: Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:

Remove and wash clothing before reuse. Wash hands before eating,
smoking or using the washroom.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Flammable - Keep away from
heat, sparks and flame. Do not store in areas of excess water vapor.

OTHER PRECAUTIONS:

Use only with adequate ventilation. Avoid prolonged contact with skin and breathing of vapor spray mist or sanding dust. Close container after each use. Keep out of reach of children. Do not take internally.

SECTION XX

HMIS (Hazardous Materials Identification System) (R) NPCA

HMIS is a recognized workplace Hazard Communications System as required by OSHA(40 CFR 1910. 1200). Information on establishing a complaint hazardous communication program using HMIS is available from:

American Labelmark Co., Inc., Labelmaster Division
5724 N. Pulaski Rd., Chicago, IL 60646
1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings; the contractor/ employer has ultimate responsibility for HMIS rating where this system is used.

Personal Protection: This code is left on application technique and the workplace ventilation. Please read Sections II through IX of this MSDS before deciding on appropriate protective equipment and beginning work. There are codes available for this section which can be obtained from Labelmaster.

This product contains at least one toxic chemical listed in Section II that is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To- Know Act of 1986 and 40 CR 372.