

MONSEY PRODUCTS -- GOLD MEDAL MB FLASHING CEMENT - ASPHALT COMPOUND
MATERIAL SAFETY DATA SHEET
MONSEY PRODUCTSNSN: 804000N052499
Manufacturer's CAGE: 6W507
Part No. Indicator: A
Part Number/Trade Name: GOLD MEDAL MB FLASHING CEMENT

=====
General Information
=====

Item Name: ASPHALT COMPOUND
Company's Name: MONSEY PRODUCTS CO
Company's Street: COLD STREAM RD
Company's P. O. Box: 368
Company's City: KIMBERTON
Company's State: PA
Company's Country: US
Company's Zip Code: 19442
Company's Emerg Ph #: 215-933-8888
Company's Info Ph #: 215-933-8888
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 002
Status: SMJ
Date MSDS Prepared: 20DEC89
Safety Data Review Date: 25AUG94
MSDS Serial Number: BVMKR
Hazard Characteristic Code: NK

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: STODDARD SOLVENT; (PETROLEUM DISTILLATES)
Ingredient Sequence Number: 01
Percent: 50
NIOSH (RTECS) Number: WJ8925000
CAS Number: 8052-41-3
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM

Proprietary: NO
Ingredient: SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC; (AROMATIC
HYDROCARBON MIXTURE) (PETROLEUM DISTILLATE)
Ingredient Sequence Number: 02
NIOSH (RTECS) Number: WF3400000
CAS Number: 64742-95-6
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)
Other Recommended Limit: 10 PPM (MFR)

=====
Physical/Chemical Characteristics
=====

Appearance And Odor: BLACK FLUID; ODOR CHARACTERISTIC OF PETROLEUM
SOLVENT.
Boiling Point: >310F,>154C
Melting Point: N/A
Vapor Pressure (MM Hg/70 F): 2 @ 68F
Vapor Density (Air=1): HVR/AIR
Specific Gravity: 1.15 (FP N)

Evaporation Rate And Ref: SLOWER THAN BUTYL ACETATE
Solubility In Water: NONE

=====
Fire and Explosion Hazard Data
=====

Flash Point: 105F,41C
Flash Point Method: SCC
Lower Explosive Limit: 0.9%
Upper Explosive Limit: 6%
Extinguishing Media: FOAM, CO*2, DRY CHEMICAL, WATER FOG, SPRAY.
Special Fire Fighting Proc: USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N).
Unusual Fire And Expl Hazrds: DO NOT MIX/STORE W/STRONG OXIDANTS LIKE LIQ CHLORINE/OXYGEN. KEEP CNTNRS TIGHTLY CLSD. CLSD CNTNRS MAY EXPLODE WHEN EXPOS TO EXTREME HEAT. APPLICATION (SUPDAT)

=====
Reactivity Data
=====

Stability: YES
Cond To Avoid (Stability): NONE SPECIFIED BY MANUFACTURER.
Materials To Avoid: STRONG OXIDANTS.
Hazardous Decomp Products: FUMES, SMOKE & CO*2, CARBON MONOXIDE IF COMBUSTION IS COMPLETE.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): NOT RELEVANT

=====
Health Hazard Data
=====

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: NO
Health Haz Acute And Chronic: OVEREXPOSURE TO VAPORS MAY CAUSE EYE IRRITATION, DIZZINESS, HEADACHES & EVEN UNCONSCIOUSNESS. REPEATED SKIN CONTACT CAN CAUSE DERMATITIS. MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY & POSSIBLY DEATH.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NOT RELEVANT
Signs/Symptoms Of Overexp: SEE HEALTH HAZARDS.
Med Cond Aggravated By Exp: NONE SPECIFIED BY MANUFACTURER.
Emergency/First Aid Proc: EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD (FP N). INHAL:REMOVE FROM VAPOR IMMEDIATELY. IF OVERCOME, CALL MD. IF BREATHING STOPPED OR IRREGULAR, START RESUSCITATION AS NEEDED. SKIN:REMOVE CONTAMINATED CLOTHES & WASH W/WATERLESS HANDCLEANER & SOAP & WATER. INGEST:DO NOT INDUCE VOMITING.

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: REMOVE SOURCES OF IGNIT. KEEP PEOPLE AWAY. RECOVER FREE LIQ. ADD ABSORB (SAND, EARTH, SAWDUST, ETC) TO SPILL AREA. AVOID BRTHG VAPS. VENTILATE CONFINED SPACES. OPEN ALL WINDOWS & DOORS. KEEP PRODS OUT OF SEWERS & WATERCOURSES BY DIKING/ (SUPP DATA)
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
Waste Disposal Method: ASSURE CONFORMITY W/APPLICABLE FEDERAL, STATE &

LOCAL DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY.

Precautions-Handling/Storing: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, FLAME OR STRONG OXIDANTS. ADEQUATE VENTILATION REQUIRED.

Other Precautions: AVOID BREATHING VAPORS. AVOID PROLONGED OR REPEATED CONTACT W/SKIN.

Control Measures

Respiratory Protection: USE NIOSH/MSHA APPROVED HYDROCARBON VAPOR CANISTER OR SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES - IF NEEDED.

Ventilation: LOCAL EXHAUST: FACE VELOCITY 60 FPM. USE ONLY W/ADEQUATE VENTILATION. USE EXPLOSION-PROOF EQUIPMENT.

Protective Gloves: CHEMICAL-RESISTANT GLOVES.

Eye Protection: ANSI APPROVED CHEM WORK GOGG (FP N).

Other Protective Equipment: USE CHEMICAL-RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEATED OR PROLONGED SKIN CONTACT.

Work Hygienic Practices: REMOVE CONTAM CLOTHG & LAUNDRY BEFORE REUSE.

REMOVE CONTAM SHOES & THORO DRY BEFORE REUSE. WASH THORO W/SOAP & (SUPDAT)

Suppl. Safety & Health Data: EXPLOR HAZ: TO HOT SURFS REQS SPECIAL PRECS.

DURING EMER CNDTNS, OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ. SYMPS MAY NOT BE IMMEDIATE APPARENT. OBTAIN MED ATTN. SPILL PROC: IMPOUNDING ELSE ADVISE AUTHS. HYGIENE PRACT: WATER AFTER CONTACT.

Transportation Data

Disposal Data

Label Data

Label Required: YES

Technical Review Date: 30AUG94

Label Date: 25AUG94

Label Status: G

Common Name: GOLD MEDAL MB FLASHING CEMENT

Chronic Hazard: NO

Signal Word: WARNING!

Acute Health Hazard-Moderate: X

Contact Hazard-Slight: X

Fire Hazard-Moderate: X

Reactivity Hazard-None: X

Special Hazard Precautions: ACUTE: OVEREXPOSURE TO VAPORS MAY CAUSE EYE IRRITATION, DIZZINESS, HEADACHES & EVEN UNCONSCIOUSNESS. REPEATED SKIN CONTACT CAN CAUSE DERMATITIS. MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY & POSSIBLY DEATH. CHRONIC: NONE LISTED BY MANUFACTURER.

Protect Eye: Y

Protect Skin: Y

Protect Respiratory: Y

Label Name: MONSEY PRODUCTS CO

Label Street: COLD STREAM RD

Label P.O. Box: 368

Label City: KIMBERTON

Label State: PA
Label Zip Code: 19442
Label Country: US
Label Emergency Number: 215-933-8888