

UNITED STATES GYPSUM -- COVER COAT DRYWALL COMPOUND USG-TAPING - JOINT
COMPOUND

MATERIAL SAFETY DATA SHEET

UNITED STATES GYPSUMSN: 561000F009747

Manufacturer's CAGE: 61357

Part No. Indicator: A

Part Number/Trade Name: COVER COAT DRYWALL COMPOUND USG-TAPING

=====
General Information
=====

Item Name: JOINT COMPOUND

Company's Name: UNITED STATES GYPSUM COMPANY

Company's Street: 101 S. WACKER DRIVE

Company's City: CHICAGO

Company's State: IL

Company's Zip Code: 60606

Company's Emerg Ph #: (312) 606-4000

Company's Info Ph #: (312) 606-4000

Record No. For Safety Entry: 001

Tot Safety Entries This Stk#: 001

Date MSDS Prepared: 19DEC88

Safety Data Review Date: 26FEB90

Preparer's Company: UNITED STATES GYPSUM COMPANY

Preparer's St Or P. O. Box: 101 S. WACKER DRIVE

Preparer's City: CHICAGO

Preparer's State: IL

Preparer's Zip Code: 60606

MSDS Serial Number: BHNKT
=====

Ingredients/Identity Information
=====

Proprietary: NO

Ingredient: CALCIUM CARBONATE (MARBLE) (LIMESTONE)

Ingredient Sequence Number: 01

Percent: 50-85%

NIOSH (RTECS) Number: EV9580000

CAS Number: 1317-65-3

OSHA PEL: 15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

Proprietary: NO

Ingredient: MICA - SILICATES (< 1% CRYSTALLINE SILICA)

Ingredient Sequence Number: 02

Percent: 0-12%

NIOSH (RTECS) Number: VV8760000

CAS Number: 12001-26-2

OSHA PEL: 20 MPPCF

ACGIH TLV: 3 MG/M3 RDUST; 9293

Proprietary: NO

Ingredient: TALC (CONTAINING NO ASBESTOS)

Ingredient Sequence Number: 03

Percent: 0-10%

NIOSH (RTECS) Number: WW2710000

CAS Number: 14807-96-6

OSHA PEL: 2 MG/M3 RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9192

Proprietary: NO
Ingredient: PERLITE
Ingredient Sequence Number: 04
Percent: 0-10%
NIOSH (RTECS) Number: SD5254000
CAS Number: 93763-70-3
OSHA PEL: 15 MG/M3 TDUST
ACGIH TLV: 10 MG/M3 TDUST; 9192

Proprietary: NO
Ingredient: KAOLIN
Ingredient Sequence Number: 05
Percent: 0-3%
NIOSH (RTECS) Number: GF1670500
CAS Number: 1332-58-7
OSHA PEL: 15 MG/M3 TDUST
ACGIH TLV: 2 MG/M3 TDUST; 9293

Proprietary: NO
Ingredient: SILICA, CRYSTALLINE - QUARTZ
Ingredient Sequence Number: 06
Percent: 0-2%
NIOSH (RTECS) Number: VV7330000
CAS Number: 14808-60-7
OSHA PEL: SEE TABLE Z3
ACGIH TLV: 0.1 MG/M3 RDUST; 9293
Other Recommended Limit: 0.05 MG/CUM NIOSH

Proprietary: NO
Ingredient: PLASTER OF PARIS (CALCIUM SULFATE DIHYDRATE)
Ingredient Sequence Number: 07
Percent: 50-85%
NIOSH (RTECS) Number: EW4150000
CAS Number: 10101-41-4
OSHA PEL: 15 MG/M3 TDUST
ACGIH TLV: 10 MG/M3 TDUST; 9293
=====

Physical/Chemical Characteristics

=====

Appearance And Odor: OFF WHITE PASTE, LOW ODOR.
Specific Gravity: 1.6
Percent Volatiles By Volume: 35%
=====

Fire and Explosion Hazard Data

=====

Flash Point: NONE
Extinguishing Media: NOT COMBUSTIBLE
Special Fire Fighting Proc: NONE
Unusual Fire And Expl Hazrds: NONE
=====

Reactivity Data

=====

Stability: YES
Hazardous Decomp Products: THIS PRODUCT CONTAINS MICA & TALC PLUS A SMALL AMOUNTS OF NATURALLY OCCURING CRYSTALLINE SILICA.
Hazardous Poly Occur: NO

=====
Health Hazard Data
=====

Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: NO
Health Haz Acute And Chronic: EYES: IRRITATION. INHALATION: NOSE, THROAT &
UPPER RESPIRATORY IRRITATION.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NONE
Signs/Symptoms Of Overexp: EYES: IRRITATION. INHALATION: NOSE, THROAT, &
UPPER RESPIRATORY IRRITATION. LUNG DAMAGE (PULMONARY FIBROSIS OR
SILICOSIS). TARGET ORGAN: LUNGS
Med Cond Aggravated By Exp: PRE-EXISTING UPPER RESPIRATORY & LUNG DISEASE
SUCH AS, BUT NOT LIMITED TO BRONCHITIS, EMPHYSEMA & ASTHMA.
Emergency/First Aid Proc: EYES: FLUSH THOROUGHLY W/WATER TO REMOVE
PARTICLES. INHALATION: REMOVE TO FRESH AIR. SKIN: WASH W/SOAP & WATER.
INGESTION: CALL PHYSICAN.

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: SCOOP UP. WASH DOWN AREA BEFORE MATERIAL
DRIES.
Waste Disposal Method: DISPOSE TO SANITARY LANDFILL IN ACCORDANCE W/
FEDERAL, STATE & LOCAL REGULATIONS.
Precautions-Handling/Storing: WHEN FINISHING JOINTS USING THESE PRODUCTS,
WET SANDING IS RECOMMENDED. STORE IN A COOL, DRY PLACE. AVOID FREEZING.

=====
Control Measures
=====

Respiratory Protection: IF DRY SANDED, USE A NIOSH APPROVED DUST
RESPIRATOR.
Ventilation: MECHANICAL/LOCAL EXHAUST
Eye Protection: SAFETY GLASSES
Suppl. Safety & Health Data: CONTAINS CALCIUM CARBONATE OR GYPSUM.

=====
Transportation Data
=====

=====
Disposal Data
=====

=====
Label Data
=====

Label Required: YES
Label Status: G
Common Name: COVER COAT DRYWALL COMPOUND USG-TAPING
Special Hazard Precautions: EYES: IRRITATION. INHALATION: NOSE, THROAT &
UPPER RESPIRATORY IRRITATION. EYES: IRRITATION. INHALATION: NOSE, THROAT, &
UPPER RESPIRATORY IRRITATION. LUNG DAMAGE (PULMONARY FIBROSIS OR
SILICOSIS). TARGET ORGAN: LUNGS
Label Name: UNITED STATES GYPSUM COMPANY
Label Street: 101 S. WACKER DRIVE
Label City: CHICAGO
Label State: IL

Label Zip Code: 60606

Label Emergency Number: (312) 606-4000