

DYNATRON BONDO -- 908 EPOXY GLUE - ADHESIVE RESIN  
MATERIAL SAFETY DATA SHEET  
DYNATRON BONDONS: 804000F020037  
Manufacturer's CAGE: 16522  
Part No. Indicator: A  
Part Number/Trade Name: 908 EPOXY GLUE

=====  
General Information  
=====

Item Name: ADHESIVE RESIN  
Company's Name: DYNATRON/BONDO CORP  
Company's Street: 3700 ATLANTA INDUSTRIAL PKY NW  
Company's City: ATLANTA  
Company's State: GA  
Company's Zip Code: 30331-1098  
Company's Emerg Ph #: (404) 696-2730 OR 971-1502  
Company's Info Ph #: (404) 696-2730 OR (800) 241-3386  
Record No. For Safety Entry: 001  
Tot Safety Entries This Stk#: 002  
Date MSDS Prepared: 26JUN88  
Safety Data Review Date: 26DEC91  
MSDS Preparer's Name: S. ABDUL RAZZAK  
Preparer's Company: DYNATRON/BONDO CORP  
Preparer's St Or P. O. Box: 3700 ATLANTA INDUSTRIAL PKY NW  
Preparer's City: ATLANTA  
Preparer's State: GA  
Preparer's Zip Code: 30331-1098  
MSDS Serial Number: BMHPT

=====  
Ingredients/Identity Information  
=====

Proprietary: NO  
Ingredient: BISPHENOL A DIGLYCIDYL ETHER RESIN, EPOXY RESIN, ARALDITE  
6004, 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN  
Ingredient Sequence Number: 01  
Percent: >50%  
NIOSH (RTECS) Number: KD4380000  
CAS Number: 25068-38-6

=====  
Physical/Chemical Characteristics  
=====

Appearance And Odor: CLEAR W/SLIGHT ODOR  
Boiling Point: >392F  
Vapor Pressure (MM Hg/70 F): 1  
Specific Gravity: 1.17  
Solubility In Water: INSOLUBLE  
Percent Volatiles By Volume: 0%

=====  
Fire and Explosion Hazard Data  
=====

Flash Point: 490F  
Flash Point Method: CC  
Extinguishing Media: CO2, FOAM, DRY CHEMICAL, OR WATER SPRAY  
Special Fire Fighting Proc: WEAR SELF-CONTAINED BREATHING APPARATUS.

=====  
Reactivity Data  
=====

Stability: YES  
Cond To Avoid (Stability): ELEVATED TEMPERATURES  
Materials To Avoid: STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES IN BULK  
Hazardous Decomp Products: CO, CO2, ALDEHYDES, & OTHER TOXIC PRODUCTS  
Hazardous Poly Occur: NO

=====  
Health Hazard Data  
=====

LD50-LC50 Mixture: ORAL LD50 (RAT): >10,000 MG/KG.  
Route Of Entry - Inhalation: YES  
Route Of Entry - Skin: YES  
Route Of Entry - Ingestion: NO  
Health Haz Acute And Chronic: EYES: IRRITATION. SKIN: DERMATITIS,  
SENSITIZATION, & ALLERGIC REACTION.  
Carcinogenicity - NTP: NO  
Carcinogenicity - IARC: NO  
Carcinogenicity - OSHA: NO  
Explanation Carcinogenicity: NONE  
Signs/Symptoms Of Overexp: EYES: IRRITATION. SKIN: DERMATITIS, ALLERGIC  
REACTION, & SENSITIZATION.  
WSSH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF  
BREATHING IS DIFFICULT. INGESTION: IF CONSCIOUS, GIVE LARGE QUANTITIES OF  
WATER. INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Precautions for Safe Handling and Use  
=====

Steps If Matl Released/Spill: REMOVE W/INERT ABSORBENT. PLACE MATERIAL IN  
CLOSABLE CONTAINER FOR DISPOSAL. FLUSH CONTAMINATED AREA W/WATER.  
Waste Disposal Method: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL  
REGULATIONS.  
Precautions-Handling/Storing: STORE IN COOL, DRY AREA. KEEP PRODUCT CAPPED  
WHEN NOT IN USE. USE W/GOOD VENTILATION. KEEP FROM STRONG ACIDS OR BASES IN  
BULK.  
Other Precautions: AVOID CONTACT W/SKIN/EYES & CLOTHING. AVOID BREATHING  
VAPORS.

=====  
Control Measures  
=====

Ventilation: ADEQUATE  
Protective Gloves: IMPERVIOUS SUCH AS NATURAL RUBBER  
Eye Protection: SAFETY GLASSES OR GOGGLES  
Other Protective Equipment: BARRIER CREAM  
Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE. WASH HANDS THOROUGHLY AFTER EACH USAGE.

=====  
Transportation Data  
=====

=====  
Disposal Data  
=====

=====  
Label Data  
=====

Label Required: YES  
Label Status: G  
Common Name: 908 EPOXY GLUE  
Special Hazard Precautions: EYES: IRRITATION. SKIN: DERMATITIS,

SENSITIZATION, & ALLERGIC REACTION. EYES: IRRITATION. SKIN: DERMATITIS,  
ALLERGIC REACTION, & SENSITIZATION.

Label Name: DYNATRON/BONDO CORP

Label Street: 3700 ATLANTA INDUSTRIAL PKY NW

Label City: ATLANTA

Label State: GA

Label Zip Code: 30331-1098

Label Emergency Number: 404) 696-2730 OR 971-1502